LISTING OF CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the

application.

Please amend claims 7, 8, and 10 as follows.

1-3. (canceled)

4. (Previously presented) A method of manufacturing an emulsion of water and fuel

using a series of batch processing steps comprising:

(a) charging a fuel and an additive into a mixing tank;

(b) agitating the fuel and the additive charged into the mixing tank;

(c) charging water into the mixing tank and forming a mixture solution of the fuel,

additive and water;

(d) reducing cluster sizes of the fuel and water in the mixture solution by pumping the

mixture solution through a processing means and returning the mixture solution into the mixing

tank;

(e) separating the mixture solution in the mixing tank and forming a water rich portion of

the mixture solution at a bottom portion of a mixing tank; and

(f) emulsifying the mixture solution from the bottom portion of the mixing tank at first

through the processing means and returning the mixture solution to the mixing tank, thereby

forming the emulsion of water and fuel.

- 2 -

5. (Previously presented) The method of manufacturing the emulsion of water and fuel

according to claim 4, wherein the water rich portion of the mixture solution is firstly emulsified

in step (f) by pumping through the processing means prior to another portion of the mixture

solution being emulsified in step (f) by pumping through the processing means.

6. (Previously presented) The method of manufacturing the emulsion of water and fuel

according to claim 4, wherein agitating of the fuel, additive and water in the mixing tank is

simultaneously performed with the reducing cluster sizes of the fuel and water.

7. (Currently amended) A method of manufacturing an emulsion of water and fuel using

a series of batch processing steps comprising:

(a) charging a fuel and an additive into a mixing tank containing the emulsion of water

and fuel having a first volume;

(b) agitating the water emulsion of water and fuel having a first volume together with the

fuel and additive and forming a first mixture solution;

(c) charging water into the mixing tank and forming a second mixture solution; and

(d) emulsifying the second mixture solution by pumping the second mixture solution

from the mixing tank through a processing means, which reduces eluster-sizes of the fuel-and the

water clusters of liquid molecules in the mixture solution into smaller clusters, and returning the

resulting emulsion of water and fuel having a second volume larger than the first volume to the

mixing tank.

2

Application S.N. 10/615,801

Attorney Docket No.: VX032544

8. (Currently amended) A method of manufacturing an emulsion of water and fuel using

a series of batch processing steps comprising:

(a) charging a fuel and an additive into a mixing tank;

(b) agitating the fuel and the additive charged into the mixing tank and forming a mixed

solution of the fuel and additive;

(c) charging and mixing water into the mixing tank and forming a first mixture solution

of the fuel, additive and water;

(d) reducing <del>cluster sizes of the fuel and water</del> clusters of liquid molecules in the first

mixture solution into smaller clusters by pumping the firstly mixed solution through a processing

means and returning to the mixing tank, thereby forming a second mixture solution of the fuel,

additive and water;

(e) separating the second mixture solution in the mixing tank and forming a water rich

portion in the second mixture solution at a bottom portion of a mixing tank; and

(f) emulsifying the separated second mixture solution from the bottom portion of the

mixing tank at first through the processing means, thereby forming the emulsion of water and

fuel.

1 1 1

9. (Previously presented) The method of manufacturing water emulsion fuel according to

claim 8, wherein the water rich portion of the second mixture solution is firstly emulsified in step

(f) by pumping through the processing means prior to another portion of the second mixture

solution being emulsified in step (f) by pumping through the processing means.

10. (Currently amended) The method of manufacturing water emulsion fuel according to claim 8, wherein agitating of the fuel, additive and water in the mixing tank is simultaneously performed with the reducing cluster sizes of the fuel and water step (c) and step (d) are performed in parallel.

1. 1. 1. 1. 1. 1.